



# BB-3000W

Wireless Programmable Bump Bar

# BB-3000W

Specification	BB-3000W
Construction	100% true spill-proof structure, 10 programmable keys in 2 x 5 matrix.
Preprinted Keys	2 x 5 keys : SERVE / RREV / RECALL / SIDE ON / SERVE / NEXT / RECALL / SIDE OFF + 2 x Reserved

## Programmability

Coverage	10 keys
Code Type	ASCII
Language	English or European, software configured
Contents Length	56 byte(S) / key or 28 2-byte(S) / key

## Programmability

Voltage	Bump bar unit: 3VDC +/- 10% [AA alkaline battery cell x2] Dongle: 5VDC +/- 10% (Powered by USB port)
---------	---

## Mechanical

Dimensions	209.0 mm (W) x 95.0 mm (D) x 30.5 mm (H)
Weight	540g (not including battery cells)

## Communication

Wireless	RF frequency : 915MHz ; range 10m
----------	-----------------------------------

## Environmental

Operating Condition	0°C to +70°C
Storage temperature	-35°C to +80°C
Relative humidity	10 to 90%; 5 to 90%, non-condensing
Vibration	4G
Shock	40G

## Reliability Information

Push key switch	2,000,000 strokes (min.)
Applicable Conformity	FCC Class A, CE

Design and Manufacturing in Taiwan by Posiflex Technology, Inc.  
The product information and specifications are subject to change without prior notice.  
Please refer to the web site for more attachment options.

### Certifications



V1.1\_17042021

**POSIFLEX**

**POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.**

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru,

Karnataka 560093

Tel : +91 80 4078 2700 | Mob : +91 9535432110

Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller