

Your Versatile Partner



TX-5000E



TX-5000

TX-5000/5000E

Powerful Fanless POS Box

The TX-5000 Series is a high-end fanless POS Box. Incorporating leading CPU technology – 4th generation Intel Haswell processor, the TX-5000 Series provides unmatched performance while juggling multiple programs with ease.

TX-5000/5000E

High Performance

With SSD and the 4th generation Intel Haswell processor up to Core i7, the TX-5000 Series is faster, cooler and more efficient. With the patented fanless design, it delivers unparalleled performance at completely silent operation.

Compact and Hassle-free

Its small footprint design allows the device to be placed anywhere you need a Point of Service system. Built-in PoweredUSB ports free up the need for multiple power adapters for peripherals and keep the counter neat and tidy.

Expandable and Flexible

Connect to a wide range of POS peripheral options for greater productivity and flexibility to meet numerous applications.

Specification	TX-5000	TX-5000E
Processor	Intel Haswell G1820, 2.70 GHz, 2M Cache; Intel Haswell G3320TE, 2.30 GHz, 3M Cache; Intel Haswell Core i3-4330TE, 2.40 GHz, 4M Cache; Intel Haswell Core i5-4570TE, up to 3.30 GHz, 4M Cache; Intel Haswell Core i7-4770TE, up to 3.30 GHz, 8M Cache	
System Memory	DDR3L SO-DIMM x 2, max. 16GB	
Storage Device	SATA x 2, factory default SSD x 1	
RAID Function	N/A	
Intel vPro Support	N/A	
TPM	N/A	
Power Supply	12V/80W	12V/150W
OS support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request	

I/O & Expansion

Serial Port	6, DB9 x 4, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports	
Parallel Port	Yes	
Standard USB Port	8, USB 3.0 x 2 + USB 2.0 x 6	5, USB 3.0 x 2 + USB 2.0 x 3
PoweredUSB Port	N/A	3, 24V x 1 + 12V x 2
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support for Posiflex monitors; DP x 1	
CR Port	1, control 2 CR via optional Y-cable	
PS/2 Port	N/A	
Audio	Mic-in/Line-out; Optional internal 2W speaker x 1	
Expansion Slot	Mini-PCIe slot x 1	

Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 83
Weight (N. W. in kg)	2.75

Environmental

Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	Mini-PCIe WiFi/BT module
------	--------------------------

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications



V1.1_17042021

POSIFLEX

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru,

Karnataka 560093

Tel : +91 80 4078 2700 | Mob : +91 9535432110

Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller