

# WT-1010A



## System Configuration

Processor	Intel Elkhart Lake Celeron J6412
System Memory	1 x DDR4 SO-DIMM, max. 16 GB
Supported Storage	M.2 connector x 1 [SATA Signal Only]
TPM	TPM 2.0
OS Support	Windows 10 IoT 64 bits /Windows 11 IoT GAC

## Display & Touch

LCD	10.1" TFT LCD with LED backlight
Resolution	1280 x 800
Touch	PCAP supporting multi-touch

## I/O & Expansion

Serial Port	RJ50 x 1, 5V/12V supported
Standard USB Port	4, USB 3.0 x 4
LAN Port	1 x 10/100/1000 Mb
Display Port	mini HDMI
CR Port	1, control 2 x cash drawer, support 24V CR
Audio	1 x 2W speaker
Internal Expansion Slot	1 x M.2 2230 for Wi-Fi/BT

Power	12V60W Adapter
-------	----------------

Mounting	VESA 75 Stand (Stand P/N: 38326001013, Mount Kit P/N: 39646056013)
----------	--

## Dimension

W x D x H in mm	285 x 37 x 173
-----------------	----------------

## Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

## Built-In Optional

Camera	1 MP wide angle camera
--------	------------------------

\* Please note that this specification is preliminary, and is subjected to change without notice

\* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\* The product information and specifications are subject to change without prior notice.

\* Please refer to the website for more attachment options.

## Certifications



VO.1\_27092023



**POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.,**  
#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd,  
Nagavarapalya, Bengaluru, Karnataka - 560093.  
Tel: +91 80 4078 2700 | Mob : +91 9535432110  
Email: marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller



# WT-1010A

## 10.1" POS Terminal